
CAT 3

Kvadrat

Remix - 3

COMPOSIZIONE / COMPOSITION

90% lana vergine
10% nylon pettinato

/ 90% new wool, worsted 10% nylon

RESISTENZA ALL'ABRASIONE / ABRASION RESISTANCE

100,000 Martindale

RESISTENZA AL FUOCO / FLAME RETARDANCY

AS/NZS 1530.3
AS/NZS 3837 Class 2
ASTM E84 Class A Unadhered
ASTM E84 Class A Adhered
BS 5852 Crib 5 with treatment
BS 5852 Part 1
EN 1021-1/2
EN 13501 B-s2, d0 with treatment
GB 50222 B1 with treatment (Chinese)
IMO FTP Code 2010 Part 7 with treatment
IMO FTP Code 2010 Part 8
NF D 60 013
NFPA 260
ÖNORM B1/Q1
SN 198 898 5.3 with treatment
UNI 9175 1IM
US Cal. Bull. 117-2013

MANTENIMENTO E PULIZIA


/ CLEANING AND CARE



NON LAVARE
/ DO NOT WASH



NON CANDEGGIARE
/ DO NOT BLEACH



NON METTERE
IN ASCIUGATRICE
/ DO NOT TUMBLE DRY



STIRARE A TEMPERATURA
MEDIA (MAX 150°C)
/ IRON AT A MEDIUM TEMPERATURE
(MAX 150°C)



LAVAGGIO A SECCO
PROFESSIONALE
/ PROFESSIONAL DRY CLEANING