
CAT 3

Kvadrat Revive

COMPOSIZIONE / COMPOSITION

100%
poliestere riciclato FR
/ 100% recycled polyester FR

RESISTENZA ALL'ABRASIONE / ABRASION RESISTANCE

60,000 Martindale

RESISTENZA AL FUOCO / FLAME RETARDANCY

AS/NZS 3837 Class 1
ASTM E84 Class A Unadhered
ASTM E84 Class B Adhered
BS 5852 Crib 5 with treatment
BS 5852 Ignition source 3
BS 5852 Part 1 with treatment
DIN 4102 B1
EN 1021-1/2
IMO FTP Code 2010 Part 8
NFPA 701
ÖNORM B1/Q1
SN 198 898 5.3 with treatment
UNI 9175 1IM
UNI 9177 Classe 1
US Cal. Bull. 117-2013


MANTENIMENTO E PULIZIA / CLEANING AND CARE



LAVARE A MAX 60°C / 140°F
PROGRAMMA DELICATI
/ WASH AT MAX 60°C / 140°F
MILD PROCESS



NON CANDEGGIARE
/ DO NOT BLEACH



**NON METTERE
IN ASCIUGATRICE**
/ DO NOT TUMBLE DRY



**STIRARE A TEMPERATURA
MEDIA (MAX 150°C)**
/ IRON AT A MEDIUM TEMPERATURE
(MAX 150°C)



**LAVAGGIO A SECCO
PROFESSIONALE**
/ PROFESSIONAL DRY CLEANING